

GENERAL INSTALLATION INSTRUCTIONS

Tools Needed

•Stud Finder • Pencil • Level • Tape Measure

Warning: Seat must be mounted to stude in wall. If stude placement does not allow this wall must be re-enforced before installation.



- 1. Determine were the wall studs are located, by using the stud finder.

 If your studs do not line up for your seat installation you will need to install wood blocks behind the finished wall.

 For a safe installation please seek professional help.
- 2. Mark the location for your installation at desired height on wall ensuring that position is over studs. Install your shower seat approximately 17"- 21" above the shower floor, or 17"-19" for ADA compliance. If your seat has legs be sure to put legs down when choosing mounting height to ensure legs touch floor after installation.
- **3.** Using the template provided mark the locations for the mounting holes. Use shower seat if template was not provided to determine the mounting holes locations.
- **4.** Use appropriate drill bit for your wall construction to drill mounting holes, and use appropriate mounting hardware to secure the mounting brackets.
- **5.** Place bracket covers over the mounting brackets and use mounting clips to secure seat assembly in place. If included insert the seat assembly legs into the bracket cover slots.
- 6. Complete your installation by snapping the mounting pin caps into the mounting bracket covers.

Warnings

Wall construction and materials may vary from home to home. You may need to purchase appropriate mounting hardware from your local hardware store. Seek professional help to ensure a safe installation.

07/20/2018 P 847•244•1234 | www.barclayproducts.com